



# FROM **CEMB** EXPERIENCE

**ER10** balancer is the result of CEMB consolidated experience in the manufacturing of high technology garage and industrial balancers since 1946. Development and cooperation with the most important car and tyre manufacturers guarantee to the professionals in the garage equipment field:

- Reliability
- Easy and quick use
- Accuracy
- 3D measures
- Reduced cycle time!

# **INNOVATIVE DESIGN:**

# **ERGOFAST**

- With ER10, CEMB widens its range of products ERGOFAST, maintaining the concepts of ergonomics and practicality together with the original design
- WBA Wheel Best Access
   Wide space to work inside the rim
- Innovative touch screen
- Ergonomic tool positioning CLOSE AT HAND!

# ER10

# **CORE OF TECHNOLOGY**

- Automatic gauge to measure the distance and diameter of rims of up to 28" with an innovative clip
  to hold the adhesive weight
- Virtual Sonar for 3D measurements of wheels that, in cases of metal rims and absence of sonar, calculates the width of the rim
- AutoAdaptive Mode The new tolerance calculation system
- Panel with Touch system, innovative, simple and durable. Allows intuitive use of all machine functions
- Software programs for the professionals: SPLIT, OPT, ALU
- **ALU-S 3D Balancing mode** Adhesive weights on the internal rim planes with specific counterweight position indicator
- Low balancing speed. Also available in the version equipped with safety guard
- Latest generation VDD Virtual Direct Drive Super-fast and extremely accurate measuring system







- After acquiring the position of the first plane of correction, the new software Virtual Sonar calculates the width of the rim, identifying a possible range of external correction planes.
- During the measurement spin, Virtual Sonar verifies that it is possible to fall within the tolerance with the correction indicated on all possible external planes.
- If there is even one possible plane for which the required correction does not allow the residual unbalance to fall within the tolerance range (calculated with AutoAdaptive software), the machine will request manual entry of the rim width in mm.





The innovative tolerance calculation system AutoAdaptive Mode is based on the evaluation of the residual imbalance limit value corresponding to an acceptable perceived vibration. For each wheel that is balanced, the software AutoAdaptive Mode detects weight and dimensions and calculates the tolerance value that will cancel any vibration perceived on the steering wheel. AutoAdaptive Mode grants the highest comfort when driving and saves balancing time.

In 1952 Cemb created the cone adapters for balancing machines and since then the company continued developing and producing high precision centering systems for any type of wheel. Cemb does not recommend the use of non-original adapters on its balancing machines.

# STANDARD ACCESSORIES



# **UC20/2 GLM40** 41FF83150

Standard equipment composed of: 3 cones Ø 45÷110 mm, quick locknut with handwheel GLM40, width gauge, pincerhammer and 60 g counterweight.



## UC20/2 GI 40 41FF83149

Standard equipment composed of: 3 cones Ø 45÷110 mm, quick locknut GL40, width gauge, pincer-hammer and 60 g counterweight.



# **OPTIONAL ACCESSORIES** - Especially designed for car manufacturers



## **RL CUP** 41FF79255

Large plastic cup with polyurethane protection ring for light alloy rims.

# SR4 - SR5 - SR5/2 - SRUSA

Stud adapters for rim protection and high precision centering for wheels with 4 or 5 holes. Studs are made of two pieces, elastically coupled: pressure is therefore homogeneous on all the holes.

VL/2 CONE + G36 DISC 41FF86174

Kit for light truck wheels (Ø 97÷170mm central hole).

# **MT CONE** 40FF57321

High precision graduated cone for German cars (with central hole Ø 56,5 / 57 / 66,5 / 72,5 mm).

## UH20/2 41FF42048

PEUGEOT-CITROËN KIT

Universal adapter for all wheels with 3.4.5.6 holes (pitch circle Ø 95-210 mm) complete with high precision back centering double cone (Cemb patent) for wheels with/ without central hole (Renault, Peugeot and Citroën). Grants double accuracy compared to similar adapters on the market.

High precision kit composed of: 5 bushes (Ø 60 / 66 / 71 / 88 / 129,9 mm). Developed according to Renault specifications.

# MERCEDES KIT 41FF88003


High precision kit composed of: 3 cones (Ø 57- Ø 66,5 - Ø 84/85mm) + 1 pressure spring, according to Mercedes Benz specifications.

RENAULT KIT 41FF73171 41FF77152 High precision kit composed of: 1 bush  $\emptyset$  60mm + 2

FOR MORE INFORMATION SEE THE COMPLETE BROCHURE ON THE WEB SITE: www.cemb.com

cones (Ø 62  $\div$  68 mm and Ø 54  $\div$  60 mm). Developed according to Peugeot and Citroën specifications.





Single phase power supply

Max. absorbed power

Balancing speed

Measuring cycle for 15 kg (33 lb) wheel

Measurement uncertainty

Avarage noise

Rim width setting range

Rim diameter setting range

Max. wheel weight

Machine weight

115 / 230 V 50/60 Hz

0,15 kW

100 rpm

4.7 s

0,5 g

< 70 dB (A)

 $1.5" \div 20" \, / \, 40 \div 510 \; mm$ 

 $10" \div 30" / 265 \div 765 \text{ mm}$ 


< 75 kg

110 kg





# **Zero Weight Lift OPTION TO REDUCE ANY EFFORT**



For more information see the complete brochure on the web site www.cemb.com

Wheel loading and removal without effort or adjustment

# PERFECT CENTERING

Wheel automatic lifting Ideal centering and more accurate balancing

Quicker than any other traditional lift A single pedal controls the whole working cycle

# AUTOMATIC

Electronic system with PLC

## UNIVERSAL

Applicable to any CEMB balancing machine



## CEMB S.p.A.

Via Risorgimento, 9 23826 Mandello del Lario (LC) - Italy www.cemb.com





Garage equipment division **CEMB - ITALY** Plant and Training Center Phone +39 0341 706111 garage@cemb.com

