

NEW

SX119 PRO LNL



PAR-MOVE CONCEPT HIGH PERFORMANCE SUPER-AUTOMATIC LEVER - NO LEVER TYRE CHANGER WITH DUAL ASSIST ARM AND POWER X



Suitable for Tubeless tyre bead seating system (optional)



MOTOINVERTER

Faster, more accurate and reliable drive for your tyre changer.



COMING SOON...

Discover on our website!



5 YEAR WARRANTY ON POWERX, GEARBOX and PAR-MOVE

- Robust fixed vertical tower with innovative **parallelogram operating arm [Giuliano Patent]**.

- Lever-No-Lever** tyre mounting/demounting system [Giuliano Patent], (standard).



"LEVER" MODE



"NO LEVER" MODE



- Tyre inflation by pedal and Tools Storage Box (standard)

- Double rotation speed by pedal

- Tabletop thickness 14 mm with **POWERX** four cylinders clamping system [Giuliano Patent].

- Bead breaker **double effect** Cylinder ø 200 mm.

- "Easy Access" extractable pedal box for quick service



220V-1ph Inverter

Available in:

- Blue Trim
- Black Trim
- Red Trim

- Vertical tower with **built-in air tank**



- Reinforced Chassis.** Fixed vertical tower and parallelogram operating arm [Patented] makes SX119Pro LNL **extremely robust** and stiff, granting **increased rigidity** and eliminating all flexes.



HP119 Additional auxiliary helper system

(standard) provides a valuable support in mounting/demounting Run Flat, UHP and low profiled tyres.



Patented **PO SYSTEM** (standard) automatically moves the bead breaker shovel back to the starting position, after its penetration.



- Adjustable BB shovel stroke. Super-quick and Simple



A very practical **Wheel Lifter** reduces effort and increases productivity (optional).



STANDARD FEATURES

Rim clamping from outside	10" - 27"
Rim clamping from inside	12" - 29"
Max. tyre diameter	1100 mm (43")
Max. tyre width	415 mm (16")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 Bar (145 Psi)
Power supply	400V-3ph-2 speed 220V-1ph/220V-1ph-2 speed
Motor power	0,8 / 1,1 kW (3 ph)
Rotation speed	7 - 14 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	428 kg
Max. overall dimensions	1390x1350x2170 mm

STANDARD ACCESSORIES



EXTENSIVE SELECTION OF STANDARD ACCESSORIES

Bead lifting lever • Lube paste bucket and Brush • Plastic protectors for LNL mounting/demounting tool • 2 Protectors for bead breaker shovel • Jaw protectors for alloy rims • Lubricator + Pressure regulator • Bucket support